

Motion detectors

IS 345 MX Highbay

V3 KNX - surface, sq.
EAN 4007841 058296



infrared sensor
360°



max. 30 x 4 m



KNX



IP54



2 - 1000 lux



1-255 min



ideal 4 - 14 m



Teach mode



energy saving



5 JAHRE
HERSTELLER
GARANTIE
www.steinel.de/garantie
manufacturer's
warranty
steinel-professional.de/garantie

Function description

Surveillance on the highest level. Infrared motion detector IS 345 MX Highbay for indoors, ideal for large heights in depots, high-bay warehouses, machine shops, check-in areas and departure lounges, installation height 14 m, detection zone 30 x 4 m (radial), large terminal compartment for easy installation. Available as square surface-mounted and concealed version.

Technical specifications

Type	Motion detectors
Dimensions (L x W x H)	95 x 95 x 65 mm
Power supply, detail	KNX bus
Sensor Technology	passive infrared
Application, place	Indoors
Application, place, room	high-bay warehouse, Indoors
Installation site	ceiling
Installation	Surface wiring
Electronic scalability	No
Mechanical scalability	No
Mounting height	4,00 – 14,00 m
Optimum mounting height	12 m
Detection angle	360 °
Angle of aperture	9 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes

Reach, radial	30 x 4 m (120 m ²)
Twilight setting TEACH	Yes
Twilight setting	2 – 1000 lx
Time setting	0 sec. – 1092 min
Basic light level function	Yes
KNX functions	Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 2x, Presence output, Day / night function
With bus coupling	Yes
Settings via	ETS software, Remote control, Bus, Smart Remote
IP-rating	IP54
Material	Plastic
Colour	white
Colour, RAL	9003
Manufacturer's Warranty	5 years
Version	KNX - surface, sq.
PU1, EAN	4007841058296

Motion detectors

IS 345 MX Highbay


V3 KNX - surface, sq.
EAN 4007841 058296

STEINEL[®]
PROFESSIONAL

Accessories

EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 592912	User remote control RC7 KNX

Detection Zone



Mögliche Montagehöhe: 4,00 m – 14,00 m
Orange: radial und tangential

Dimension Drawing

