

Photo-cell controller

# Light Sensor Dual

V3 KNX - surface, sq.  
EAN 4007841 058319

**STEINEL**<sup>®</sup>  
PROFESSIONAL



max. 4 m



Twilight switch +  
eco-mode



KNX



IP54



2 - 1000 lux



5 JAHRE  
HERSTELLER  
GARANTIE  
steinel.de/garantie



CE



VDE

## Function description

Light measurement in perfection. The Light Sensor Dual photo-cell controller with KNX interface measures directed and diffuse light, watches over areas below the sensor and measures the room brightness. Combining the measurement results reduces error influences. Available either in round or square surface-mounted and concealed version.

## Technical specifications

Type	Constant-lighting controller	Type of installation	Surface wiring
Dimensions (L x W x H)	95 x 95 x 42 mm	Mounting height	2,00 – 4,00 m
Sensor Technology	Light sensor	With bus coupling	Yes
Application, place	outdoors, Indoors	IP rating	IP54
Application, place, room	One-person office, classroom, Open-plan office, high-bay warehouse, conference room	Version	KNX - surface, sq.
Installation site	wall, ceiling	PU1, EAN	4007841058319

## Accessories

EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 592912	User remote control RC7 KNX

Photo-cell controller

# Light Sensor Dual

V3 KNX - surface, sq.  
EAN 4007841 058319



## Dimension Drawing

