

Photo-cell controller

Light Sensor Dual

V3 KNX - concealed, sq.
EAN 4007841 058326

STEINEL[®]
PROFESSIONAL



Twilight switch +
eco-mode



KNX



IP20



2 - 1000 lux



ideal 4 m



manufacturer's
warranty
steinel-professional.de/garantie



CE



VDE

Function description

Light measurement in perfection. The Light Sensor Dual photo-cell controller with KNX interface measures directed and diffuse light, watches over areas below the sensor and measures the room brightness. Combining the measurement results reduces error influences. Available either in round or square surface-mounted and concealed version.

Technical specifications

Type	Constant-lighting controller
Dimensions (L x W x H)	94 x 94 x 51 mm
Sensor Technology	Light sensor
Application, place	Outdoors, Indoors
Application, place, room	classroom, one-person office, open-plan office, high-bay warehouse, conference room / meeting room
Installation site	wall, ceiling

Type of installation	Concealed wiring
Mounting height	2,00 – 4,00 m
With bus coupling	Yes
IP rating	IP54
Version	KNX - concealed, sq.
PU1, EAN	4007841058326

Photo-cell controller

Light Sensor Dual

V3 KNX - concealed, sq.
EAN 4007841 058326



Dimension Drawing

