

iHF 3D

V3.5 KNX - black
 EAN 4007841 059637
 Article number 059637



intelligent high frequency sensor
160°



3 zones scalable 3 x 1-5m, max. 7 m



KNX



IP54



10 - 2000 lux



10 sec - 1092 min



Ideal 2 m

Teach

Teach mode



energy saving

5 years

manufacturer's warranty steinel-professional.de/garantie

Function description

Detects what you want it to. Integrates into the building network. iHF 3D KNX motion detector, ideal for facades, carports, parking areas and patios. 160° iHF-sensor with 5 m reach, 3D aerial technology, identifies and distinguishes between moving objects, no inadvertent triggering any more by small animals, very low or high temperatures. Detects everything equally well whichever direction it is approached from. The new Bluetooth version lets you start the programming mode and update the software by app.

Technical specifications

Dimensions (L x W x H)	120 x 117 x 120 mm
With motion detector	Yes
Manufacturer's Warranty	5 years
Settings via	ETS software, Bus, Bluetooth, App, Potentiometers, Smartphone
Version	KNX - black
PU1, EAN	4007841059637
Type	Motion detectors
Application, place	Outdoors
Application, room	outdoors, front door, all round the building, terrace / balcony, courtyard & driveway
Colour	black
Colour, RAL	9005
Includes corner wall mount	No
Installation site	wall
Installation	Surface wiring, Wall

HF-system	5,8 GHz
Detection angle	160 °
Angle of aperture	100 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Electronic scalability	Yes
Mechanical scalability	No
Reach, radial	r = 5 m (35 m ²)
Reach, tangential	r = 5 m (35 m ²)
Transmitter power	< 1 mW
Functions	Presence detector logic
Twilight setting	10 - 2000 lx
Time setting	10 s - 1092 Min.
Basic light level function	Yes
Basic light level function time	10s - 18h 12min 15s

iHF 3D


V3.5 KNX - black
 EAN 4007841 059637
 Article number 059637

Technical specifications

IP-rating	IP54
Ambient temperature	-20 – 50 °C
Material	Plastic
Power supply, detail	KNX bus
With bus coupling	Yes
Sensor Technology	iHF (intelligent high-frequency technology)
Mounting height	1,80 – 2,00 m
Mounting height max.	2,00 m
Optimum mounting height	1,8 m

Main light adjustable	0 - 100 %
Twilight setting TEACH	Yes
Constant-lighting control	No
KNX functions	Photo-cell controller, Basic light level function, Light level, Light output 2x, Presence output, Day / night function, Logic gate, Direction of movement, Distance, Sabotage protection
Interconnection	Yes
Type of interconnection	Master/master, Master/slave
Interconnection via	KNX bus
Rated current	30 mA

Detection Zone



Mögliche Montagehöhe: 1,80 m – 2,00 m
 Orange: radial und tangential
 3 skalierbare Achsen

Dimension Drawing

