

# IR Quattro HD 24m

COMI - in-ceiling installation white

EAN 4007841 079369

Article number 079369



Infrared sensor



Dual detection presence



Height



2170°

detection angle



Height



180°

detection angle



10°

detection angle



Worldwide



Frequency

mechanically switchable



CE

marked

## Function description

Detection no. 1: Infrared presence detector Presence Control PRO IR Quattro HD COMI for indoors, ideal for medium to large-size offices, conference and meeting rooms, classrooms and lecture theatres, sports halls and rehearsals, installation height up to 10 m, for switching light ON and OFF, 48 switching zones for the ultimate in detection quality, presence detection over a true 6.4 m<sup>2</sup>, square detection zone, mechanically scalable.

## Technical specifications

Dimensions (L x W x H)	108 x 120 x 10 mm	Optimum mounting height	2.8 m
Manufacturer's Warranty	5 years	Detection angle	360 °
Settings via	Remote control, DIP switches, Potentiometers, Smart Remote	Angle of aperture	16.0 °
With remote control	No	Sneak-by guard	Yes
Version	COMI - in-ceiling installation white	Capability of masking out individual segments	No
PUR, EAN	4007841 079369	Electrical scalability	No
Type	Presence detector	Mechanical scalability	Yes
Applcation, place	Indoors	Reach, radial	8 x 8 m (64 m <sup>2</sup> )
Applcation, room	classroom, lecture hall, open-plan office, high-bay warehouse, production facilities, conference room / meeting room, duty room, recreation room, changing room, sports hall, reception / lobby, multi-story / underground car park	Reach, tangential	20 x 20 m (400 m <sup>2</sup> )
Couleur	white	Reach, presence	8 x 8 m (64 m <sup>2</sup> )
Couleur, RAL	9010	Switching zones	48 00 switching zones
Includes corner wall mount	No	Functions	Normal / test mode, Semi-fully automatic, Pushbutton / switch mode, Manual ON / OFF-ON, Constant lighting control ON-OFF
		Time setting	30 s - 30 Min.
		Basic light level function	No