

Presence detector

## IR Quattro SLIM XS

V3 KNX

EAN 4007841058517



### Function description

### Technical specifications

Type	Presence detector
Dimensions (Ø x H)	94 x 49 mm
Mains power supply	24 – 29 V
Sensor Technology	passive infrared
Application, place	Indoors
Application, place, room	classroom, One-person office, side room
Installation site	ceiling
Type of installation	Concealed wiring
Switching zones	408 switching zones
Electronic scalability	No
Mechanical scalability	No
Mounting height	2,50 – 4,00 m
Optimum mounting height	2,8 m
Detection angle	360 °
Angle of aperture	360 °
Sneak-by guard	Yes
Reach, detail	Retina lens and hexagonal Fresnel structure
Reach, radial	4 x 4 m (16 m <sup>2</sup> )
Reach, tangential	4 x 4 m (16 m <sup>2</sup> )
Twilight setting TEACH	No

Presence detector

## IR Quattro SLIM XS

V3 KNX

EAN 4007841058517

### Technical specifications

Twilight setting	10 – 1000 lx
Basic light level function	Yes
Basic light level function time	1-255 min
With bus coupling	Yes
With remote control	Yes
Interconnection	Yes
IP rating	IP20
Material	Plastic
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	5 years
Version	KNX
PU1, EAN	4007841058517

### Mood image

