

Presence detector

Hallway

Dali - surface

EAN 4007841 058012

STEINEL[®]
PROFESSIONAL



max. 25 x 3 m



manufacturer's
warranty
steinel-professional.de/garantie



CE



VDE



max. 25 x 3 m



manufacturer's
warranty
steinel-professional.de/garantie



CE



VDE

Function description

The cleverer hallway sensor knows more. Hallway identifies the direction of movement and know whether someone is approaching or leaving. It can also tell whether person present are on the right or left. Perfect radial detection up to 25 m – ideal for long corridors and hallways. Reach can be adjusted in both directions. Contemporary True Presence® design. Featuring Bluetooth technology. Interfaces for COM 1, COM 2, DALI and KNX.

Technical specifications

Type	Presence detector
Dimensions (L x W x H)	123 x 123 x 62 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Power consumption	0,7 W
Sensor Technology	High frequency
Application, place	Indoors
Application, place, room	corridor, aisle
Installation site	ceiling
Type of installation	Surface wiring
HF-system	5,8 GHz
Electronic scalability	Yes
Mechanical scalability	No
Mounting height	2 – 4 m
Optimum mounting height	2,8 m
Detection	also through glass, wood and stud walls
Detection angle	360 °
Angle of aperture	140 °
Sneak-by guard	Yes
Capability of masking out individual segments	No

Reach, radial	25 x 3 m (75 m ²)
Twilight setting TEACH	Yes
Twilight setting	2 – 1000 lx
Time setting	0 s – 30 Min.
Control output, Dali	Addressable / broadcast 64 electronic ballasts
Constant-lighting control	Yes
Basic light level function	Yes
Basic light level function time	1-60 min, all night
Settings via	Bluetooth
With remote control	No
Interconnection	Yes
IP rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	5 years
Version	Dali - surface
PU1, EAN	4007841058012

<https://www.steinell.de>

Presence detector


Hallway

Dali - surface

EAN 4007841 058012

STEINEL[®]
PROFESSIONAL

Detection Zone



Mögliche Montagehöhe: 2,00 m – 4,00 m

Orange: radial und tangential