Motion detector - Professional Line

IS 345

V3 KNX - surface, sq. EAN 4007841 058258















2 - 1000 lux











Function description

Huge reach. Infrared motion detector IS 345 for indoors and out, ideal for passageways, corridors and commonly used spaces, installation height 5 m, detection zone 12×6 m (radial) and 23×6 m (tangential), large terminal compartment for easy installation. Available either in round or square surface-mounted and concealed version.

Motion detector - Professional Line

IS 345

V3 KNX - surface, sq. EAN 4007841 058258



Technical specifications

Туре	Motion detectors
Dimensions (L x W x H)	65 x 95 x 95 mm
Power supply, detail	KNX bus
Sensor Technology	passive infrared
Application, place	Outdoors, Indoors
Installation site	ceiling
Installation	Surface wiring
Mounting height	2,50 – 5,00 m
Reach, radial	12 x 6 m (72 m²)
Reach, tangential	23 x 6 m (138 m²)
Detection angle	360 °
Angle of aperture	45 °
Optimum mounting height	2,8 m
Mechanical scalability	No
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Electronic scalability	No
Twilight setting TEACH	Yes

Twilight setting	2 – 1000 lx	
Time setting	0 s – 1092 Min.	
Constant-lighting control	Yes	
Basic light level function	Yes	
KNX functions	Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 2x, Presence output, Day / night function, Logic gate	
With bus coupling	Yes	
Settings via	ETS software, Remote control, Bus, Smart Remote	
Interconnection	Yes	
Type of interconnection	Master/slave	
IP-rating	IP54	
Material	Plastic	
Ambient temperature	-20 – 50 °C	
Application, room	corridor / aisle, multi-storey / underground car park, outdoors, Indoors	
Colour	white	
Colour, RAL	9003	
Manufacturer's Warranty	5 years	
Version	KNX - surface, sq.	
PU1, EAN	4007841058258	

Accessories

EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 592912	User remote control RC7 KNX
EAN 4007841 056711	Black cover for IR-sensors


Motion detector - Professional Line

IS 345

V3 KNX - surface, sq. EAN 4007841 058258



Detection Zone



Mögliche Montagehöhe: 2,50 m – 5,00 m

Orange: radial Schwarz: tangential

Dimension Drawing

