

IS 3360 40m

V3 KNX - concealed, sq. black
EAN 4007841 068578
Article number 068578



infrared sensor
360°



max. 20 m



KNX



IP20



2 - 1000 lux



1 - 255 min



ideal 2,5 - 4 m

Teach

Teach mode



energy saving

5 years

manufacturer's
warranty steinel-
professional.de/
garantie

Function description

Higher, further, faster. Infrared presence detector IS 3360 for indoors and out, ideal for watching over high spaces and large areas, such as multi-storey and underground car parks, installation height up to 4 m, 360° angle of coverage, reach 20 m max. (tangential). Available either in round or square surface-mounted and concealed version.

Technical specifications

Dimensions (L x W x H)	78 x 94 x 94 mm	Optimum mounting height	2,8 m
With motion detector	Yes	Detection angle	360 °
Manufacturer's Warranty	5 years	Angle of aperture	180 °
Settings via	ETS software, Remote control, Bus, Smart Remote	Sneak-by guard	Yes
Version	KNX - concealed, sq. black	Capability of masking out individual segments	Yes
PU1, EAN	4007841068578	Electronic scalability	No
Type	Motion and Presence Detector	Mechanical scalability	No
Application, place	Indoors	Reach, radial	Ø 8 m (50 m²)
Application, room	production facilities, recreation room, changing room, function room / ancillary room, sports hall, reception / lobby, stairwell, WC / washroom, multi-storey / underground car park, warehouse, Indoors	Reach, tangential	Ø 40 m (1257 m²)
		Reach, presence	Ø 3 m (7 m²)
		Switching zones	1416 switching zones
		Twilight setting	2 – 1000 lx
		Time setting	5 s – 15 Min.
Colour	black	Basic light level function	Yes
Colour, RAL	9005	Main light adjustable	0 - 100 %
Includes corner wall mount	No	Twilight setting TEACH	Yes

IS 3360 40m

V3 KNX - concealed, sq. black
 EAN 4007841 068578
 Article number 068578



Technical specifications


Installation site	ceiling
Installation	Ceiling, Concealed wiring
IP-rating	IP20
Ambient temperature	-20 – 50 °C
Material	Plastic
Power supply, detail	KNX bus
With bus coupling	Yes
Sensor Technology	Passive infrared
Mounting height	2,50 – 4,00 m
Mounting height max.	4,00 m

Constant-lighting control	Yes
KNX functions	Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 2x, Presence output, Day / night function, Logic gate
Interconnection	Yes
Type of interconnection	Master/slave
Interconnection via	KNX bus
Rated current	12,5 mA

Accessories

EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 592912	User remote control RC7 KNX
EAN 4007841 009151	Remote control Smart Remote

Detection Zone



Mögliche Montagehöhe: 2,50 m – 4,00 m
 Orange: radial
 Schwarz: tangential

Dimension Drawing

