



# IS 3360 40m

V3 KNX - concealed, rd. black  
 EAN 4007841 068592  
 Article number 068592



5 years

manufacturer's warranty steinel-professional.de/garantie

## Function description

Higher, further, faster. Infrared motion detector IS 3360 for indoors and out, ideal for watching over high spaces and large areas, such as multi-storey and underground car parks, installation height up to 4 m, 360° angle of coverage, reach 20 m max. (tangential). Available either in round or square surface-mounted and concealed version.

## Technical specifications

Dimensions (Ø x H)	124 x 78 mm
With motion detector	Yes
Manufacturer's Warranty	5 years
Settings via	ETS software, Remote control, Bus, Smart Remote
Version	KNX - concealed, rd. black
PU1, EAN	4007841068592
Type	Motion and Presence Detector
Application, place	Indoors
Application, room	production facilities, recreation room, changing room, function room / ancillary room, sports hall, reception / lobby, stairwell, WC / washroom, multi-storey / underground car park, warehouse, Indoors
Colour	black
Colour, RAL	9005
Includes corner wall mount	No

Optimum mounting height	2,8 m
Detection angle	360 °
Angle of aperture	180 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Electronic scalability	No
Mechanical scalability	No
Reach, radial	Ø 8 m (50 m <sup>2</sup> )
Reach, tangential	Ø 40 m (1257 m <sup>2</sup> )
Reach, presence	Ø 3 m (7 m <sup>2</sup> )
Switching zones	1416 switching zones
Twilight setting	2 – 1000 lx
Time setting	5 s – 15 Min.
Basic light level function	Yes
Main light adjustable	0 - 100 %
Twilight setting TEACH	Yes

# IS 3360 40m

V3 KNX - concealed, rd. black  
 EAN 4007841 068592  
 Article number 068592

## Technical specifications


Installation site	ceiling
Installation	Ceiling, Concealed wiring
IP-rating	IP20
Ambient temperature	-20 – 50 °C
Material	Plastic
Power supply, detail	KNX bus
With bus coupling	Yes
Sensor Technology	Passive infrared
Mounting height	2,50 – 4,00 m
Mounting height max.	4,00 m

Constant-lighting control	Yes
KNX functions	Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 2x, Presence output, Day / night function, Logic gate
Interconnection	Yes
Type of interconnection	Master/slave
Interconnection via	KNX bus
Rated current	12,5 mA

## Accessories

EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 592912	User remote control RC7 KNX
EAN 4007841 009151	Remote control Smart Remote

## Detection Zone



Mögliche Montagehöhe: 2,50 m – 4,00 m  
 Orange: radial  
 Schwarz: tangential

## Dimension Drawing

