

Presence detector

HF 360

V3 KNX

EAN 4007841 059484

STEINEL[®]
PROFESSIONAL



high frequency
sensor 360°



max. Ø 12 m



KNX 4 channel



indoor sensor

TEACH

Teach mode

iQ

iQ-mode



energy saving

5 JAHRE
HERSTELLER
GARANTIE

www.steinel-professional.de/garantie

manufacturer's
warranty
steinel-professional.de/garantie



CE



VDE-GS

Function description

Doesn't miss a thing. HF-presence detector Presence Control PRO HF 360 KNX for indoors, ideal for WCs with toilet cubicles, changing rooms, stairwells, multi-storey car parks, kitchens, installation height up to 3.5 m, with digital BUS interface for controlling 4 lighting channels and HVAC, 1 – 12 m reach, reach is electronically adjustable and can be limited in two directions, detection regardless of temperature, HF-sensor technology also detects movement through glass, wood and stud walls.

Presence detector

HF 360

V3 KNX

EAN 4007841 059484



Technical specifications

Type	Presence detector
Dimensions (L x W x H)	36 x 120 x 120 mm
Mains power supply	30 V
Power consumption	0,7 W
Sensor Technology	High frequency
Application, place	Indoors
Application, place, room	function room / ancillary room, kitchenette, stairwell, WC / washroom, indoors
Installation site	ceiling
Type of installation	Concealed wiring
HF-system	5,8 GHz
Electronic scalability	Yes
Mechanical scalability	No
Mounting height	2,50 – 3,5 m
Optimum mounting height	2,8 m
Detection angle	360 °
Angle of aperture	140 °
Sneak-by guard	Yes
Capability of masking out individual segments	No
Reach, radial	Ø 16 m (201 m ²)

Twilight setting TEACH	Yes
Twilight setting	10 – 1000 lx
Time setting	0 s – 1092 Min.
Constant-lighting control	Yes
Basic light level function	Yes
Basic light level function time	1-255 min
KNX functions	Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 4x, Presence output, Day / night function
With bus coupling	Yes
With remote control	No
Interconnection	Yes
IP rating	IP20
Material	Plastic
Ambient temperature	-25 – 55 °C
Colour	white
Colour, RAL	9010
IDs, certificates	VDE
Manufacturer's Warranty	5 years
Version	KNX
PU1, EAN	4007841059484

Accessories

EAN 4007841 000363	Surface-mounting adapter Control PRO AP Box (IP54)
EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 003036	Control PRO guard cage
EAN 4007841 006600	HF-ceiling adapter
EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 592912	User remote control RC7 KNX

Presence detector


HF 360

V3 KNX

EAN 4007841 059484

STEINEL[®]
PROFESSIONAL

Detection Zone



Mögliche Montagehöhe: 2,50 m – 3,50 m
Orange: radial und tangential

Dimension Drawing

