


Photo-cell-controlled light

# LN 710 LED

Silver

EAN 4007841 053178



## Function description

Beautiful light in pure form. Quite simply, the attractive outdoor light without motion detector always cuts a fine figure whether ON or OFF. The LN 710 LED is made of UV-resistant plastic and features a modern aluminium designer-style element. The warm-white light (3000 K) sets off building walls with absolute competence. With photo-cell controller, automatic lighting at night and optional night-economy mode. Available in anthracite and silver.

## Technical specifications

Dimensions (L x W x H)	140 x 260 x 63 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Sensor Technology	Light sensor
Output	8,6 W
Interconnection	No
Slave modeselectable	No
Luminous flux	670 lm
Colour temperature	3000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Base	without
LED cooling system	Passive Thermo Control
With motion detector	No
Sneak-by guard	No
Capability of masking out individual segments	No

Electronic scalability	No
Mechanical scalability	No
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Basic light level function	No
Soft light start	No
Impact resistance	IK03
IP-rating	IP44
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Aluminium
Cover material	Plastic, opal
Manufacturer's Warranty	3 years
Settings via	Potentiometers
Cover material	sticker
Version	Silver
PU1, EAN	4007841053178

Photo-cell-controlled light

# LN 710 LED

Silver

EAN 4007841 053178



## Dimension Drawing

